

Fibre Optic Cable | TPE | chainflex® CFLG.G

36 10 million Double strokes guaranteed **10 x d** Bend radius, e-chain® **400m** Travel distance, e-chain®

- Glass-fibre cable for heaviest duty applications
- TPE outer jacket
- Oil and bio-oil-resistant
- PVC and halogen-free
- Low-temperature-flexible
- Hydrolysis and microbe-resistant

Dynamic information

Bend radius	e-chain® linear flexible	minimum 10 x d
	fixed	minimum 8 x d
Temperature	e-chain® linear flexible	-40°C up to +80°C
	fixed	-50°C up to +80°C (following DIN EN 60811-504)
v max.	unsupported	10m/s
	gliding	6m/s
a max.		20m/s ²
Travel distance		Unsupported travels and up to 400m and more for gliding applications, Class 6

Cable structure

Fibre Optic Cable	9/125 µm, 50/125 µm, 62.5/125 µm fibres in gel-filled tubes.
Core structure	Gel-filled fibre sheath surrounded by GRP rods and torsion protection braid in the outer jacket.
Core identification	Fibres ▶ Product range table
Outer jacket	Low-adhesion, extremely abrasion-resistant and highly flexible TPE mixture, adapted to suit the requirements in e-chains®. Colour: jet black (similar to RAL 9005)

Basic requirements
Travel distance
Oil resistance
Torsion

low	1	2	3	4	5	6	7	highest
unsupported	1	2	3	4	5	6	≥ 400m	
none	1	2	3	4	highest			
none	1	2	3	4	±360°			

Class 7.6.4.1

Properties and approvals

UV resistance	High
Oil resistance	Oil-resistant (following DIN EN 60811-404), bio-oil-resistant (following VDMA 24568 with Plantocut 8 S-MB tested by DEA), Class 4
Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
Halogen-free	Following DIN EN 60754
UL verified	Certificate No. B129699: "igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year"
REACH	In accordance with regulation (EC) No. 1907/2006 (REACH)
Lead-free	Following 2011/65/EC (RoHS-II/RoHS-III)
Cleanroom	According to ISO Class 1. The outer jacket material of this series complies with CF9.15.07 - tested by IPA according to standard DIN EN ISO 14644-1
CE	Following 2014/35/EU
UKCA	In accordance with the valid regulations of the United Kingdom (as at 08/2021)
Info	For hanging applications, please use cables of the series CFLG.LB - see page 228!


Guaranteed service life (details see page 28-29)

Double strokes*	5 million	7.5 million	10 million
Temperature, from/to [°C]	R min. [factor x d]	R min. [factor x d]	R min. [factor x d]
-40/-30	12.5	13.5	14.5
-30/+70	10	11	12
+70/+80	12.5	13.5	14.5

* Higher number of double strokes? Service life calculation online ▶ www.igus.eu/chainflexlife

Typical application areas

- For heavy-duty applications, Class 7
- Unsupported travels and up to 400m and more for gliding applications (horizontal), Class 6
- Almost unlimited resistance to oil, also with bio-oils, Class 4
- No torsion, Class 1
- Maximum EMC protection, with high transmission qualities
- Indoor and outdoor applications
- Crane applications, conveyor technology, low temperature applications



low	1	2	3	4	5	6	7	highest
unsupported	1	2	3	4	5	6	≥ 400m	
none	1	2	3	4	highest			
none	1	2	3	4	±360°			



Example image

Part No.	Number of fibres/ Fibre diameter	Outer diameter (d) max. [mm]	Weight [kg/km]
CFLG.6G.62.5/125.TC	6x62.5/125	10.0	80
CFLG.12G.62.5/125.TC	12x62.5/125	10.0	80
CFLG.6G.50/125.TC ¹¹⁾	6x50/125	10.0	60
CFLG.12G.50/125.TC	12x50/125	10.0	75
CFLG.12E.9/125.TC	12x9/125	10.0	75

¹¹⁾ Phase-out model

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.

Part No.	Bandwidth [MHz x km] @ 850nm	Attenuation [dB/km] @ 850nm	Bandwidth [MHz x km] @ 1,300nm	Attenuation [dB/km] @ 1,300nm
CFLG.6G.62.5/125.TC	≥ 200	≤ 3.5	≥ 500	≤ 1.0
CFLG.12G.62.5/125.TC	≥ 200	≤ 3.5	≥ 500	≤ 1.0
CFLG.6G.50/125.TC	≥ 500	≤ 3.0	≥ 500	≤ 1.0
CFLG.12G.50/125.TC	≥ 500	≤ 3.0	≥ 500	≤ 1.0

Part No.	Attenuation [dB/km] @ 1,310nm	Chromatic dispersion [ps/nm/km] @ 1,310nm	Attenuation [dB/km] @ 1,550nm	Chromatic dispersion [ps/nm/km] @ 1,550nm
CFLG.12E.9/125.TC	≤ 0.35	3.5	≤ 0.25	18

Part No.	Fibre identification	Hollow core identification
CFLG.6G.62.5/125.TC	ecru, yellow, green, red, violet, blue	orange
CFLG.12G.62.5/125.TC	ecru, yellow, green, red, violet, blue, turquoise, grey, brown, black, orange, pink	orange
CFLG.6G.50/125.TC	ecru, yellow, green, red, violet, blue	blue
CFLG.12G.50/125.TC	ecru, yellow, green, red, violet, blue, turquoise, grey, brown, black, orange, pink	blue
CFLG.12E.9/125.TC	ecru, yellow, green, red, violet, blue, turquoise, grey, brown, black, orange, pink	yellow



Cables available in the chainflex® CASE

Simple savings on delivery, storage space and re-ordering with the chainflex® CASE - ship'n store by igus®.

More on this on page 24/25 and online: www.igus.eu/cf-case



Order example: CFLG.6G.62.5/125.TC - to your desired length (0.5m steps)
CFLG.G chainflex® series 6G Number of fibres 62.5/125 Fibre diameter.TC Special marking

Order online ► www.igus.eu/CFLGG

Delivery time 24hrs or today.
Delivery time means time until goods are shipped.

cost down...



...life up

Reduce cost, improve technology, now!

Do the chainflex® price check ...

www.igus.eu/cf-price-check

... for example: Reduce bend radius with CFLG.LB ...



chainflex® fibre optic cable in a sea lock



igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year

