

Motor cable for top drive applications | PUR
chainflex® CFSPECIAL.562.PE





- For top drive applications
- For heavy duty applications
- PUR outer jacket
- Oil-resistant and coolant-resistant
- Flame-retardant
- PVC and halogen-free
- UV-resistant
- Hydrolysis and microbe-resistant

Now with DNV
approval for
top drive hanging
applications
up to 50m

Dynamic information

	Bend radius	e-chain® linear	minimum 10 x d
		flexible	minimum 8 x d
		fixed	minimum 5 x d
	Temperature	e-chain® linear	-25°C up to +80°C
		flexible	-40°C up to +80°C (following DIN EN 60811-504)
		fixed	-50°C up to +80°C (following DIN EN 50305)
	v max.	unsupported	10m/s
	a max.	sliding	2m/s
	Travel distance	For top drive hanging applications up to 50m	















Cable structure

	Conductor	Conductor cable consisting of pre-leads (following DIN EN 60228).
	Core insulation	Mechanically high-quality TPE mixture.
	Core identification	Green-yellow
	Outer jacket	1. Outer jacket: PUR mixture adapted to suit the requirements in e-chains®. Reinforcement: High tensile strength aramid braid embedded in the outer jacket. 2. Outer jacket: Low-adhesion, halogen-free PUR mixture, highly abrasion and bending-resistant, adapted to suit the requirements in top drive hanging applications (following DIN EN 50363-10-2). Colour: jet black (similar to RAL 9005)

Electrical information

	Nominal voltage	600/1,000V (following DIN VDE 0298-3)
	Testing voltage	4,000V (following DIN EN 50395)

Properties and approvals

	UV resistance	High
	Oil resistance	Oil-resistant (in accordance with DIN EN 50363-10-2)
	Offshore	MUD-resistant following NEK 606 - status 2016
	Flame-retardant	According to IEC 60332-1-2, Cable Flame, VW-1, FT1, FT2 / Horizontal Flame
	Silicone-free	Free from silicone which can affect paint adhesion (following PV 3.10.7 – status 1992)
	Halogen-free	Following DIN EN 60754
	UL verified	Certificate No. B129699: „igus 36-month chainflex cable guarantee and service life calculator based on 2 billion test cycles per year“
	UL/CSA AWM	See data sheet for details ► www.igus.eu/CFSPECIAL562PE
	NFPA	Following NFPA 79-2018, chapter 12.9
	DNV	Type Approval Certificate TAE00004G3
	REACH	In accordance with regulation (EC) No. 1907/2006 (REACH)
	Lead-free	Following 2011/65/EC (RoHS-II)
	CE	Following 2014/35/EU
	UKCA	In accordance with the valid regulations of the United Kingdom (as at 08/2021)

Typical application areas

- For high tensile loads
- Almost unlimited resistance to oil
- For top drive hanging applications up to 50m

Part No.	Number of cores and conductor nominal cross section [mm²]	Outer diameter (d) max. [mm]	Copper index [kg/km]	Weight [kg/km]
CFSPECIAL.562.PE.700.01	1G70	19.5	713	867

Note: The given outer diameters are maximum values and may tend toward lower tolerance limits.
G = with green-yellow earth core x = without earth core



EPLAN download, configurators ► www.igus.eu/CFSPECIAL562PE



EU2023

EU2023



36-month guarantee ... more than 1,350 cable types from stock ... no cutting charges 435